

Clapet de non-retour Type 805

DN50 - DN600

Données techniques

Système de fermet.:	05
Pression de service:	Max. 16 bar
Raccordement:	Montage entre-brides PN10/16
Fluides:	Eaux claires, gaz
Temp. de fluide:	Joint EPDM -10°C / +100°C Joint NBR -10°C / +80°C
Position de mont.:	horizontal, vertical ascendant et descendant

Encombrement

Art.-No.	DN	D	L	Kv [m3/h]
805 50	050	109	54	35,7
805 65	65	129	54	69
805 80	80	144	57	116
805 100	100	164	64	212
805 125	125	194	70	458
805 150	150	220	76	685
805 200	200	275	95	1447
805 250	250	330	108	2271
805 300	300	380	143	3709
805 350	350	440	184	4293
805 400	400	491	191	5837
805 450	450	541	203	6547
805 500	500	596	213	7800
805 600	600	698	222	11269

Matériaux

Corps:	DN50 - 150: DN200, DN300-400: DN350, DN450-600:	GG25, epoxy GGG40, epoxy GG25, epoxy
Joint:	DN50-300, DN400: DN350, DN450-600:	EPDM NBR
Battans:	Bronze d'alu	
Axe:	DN50-300, DN400: DN350, DN450-600:	Inox AISI 316 Inox AISI 304
Ressort:	Inox AISI 316	



