

## Clapets de non-retour

DN50 - DN200

### Type 418

#### Données techniques

|                            |                           |
|----------------------------|---------------------------|
| <b>Système de fermet.:</b> | B (Boule)                 |
| <b>Betriebsdruck:</b>      | Max.10 bar                |
| <b>Raccordement:</b>       | A brides PN10/16          |
| <b>Corps:</b>              | GGG40                     |
| <b>Fluide:</b>             | Neutres, propres liquides |
| <b>Temp. de fluide.:</b>   | Max. +80°C                |
| <b>Boule:</b>              | Revêtement NBR            |
| <b>Position de mont.:</b>  | Verticale en haut         |



#### Encombrement [mm]

| Art.-No. | A (DN) | B   | C   | D   | Kv[m³/h] | Kg   |
|----------|--------|-----|-----|-----|----------|------|
| 3140     | 50     | 200 | 165 | 173 | 71.5     | 5.5  |
| 3141     | 65     | 240 | 185 | 214 | 171.5    | 9.1  |
| 3142     | 80     | 260 | 200 | 252 | 217.5    | 13.3 |
| 3143     | 100    | 300 | 220 | 289 | 319.0    | 20.9 |
| 3144     | 125    | 350 | 250 | 368 | 745.0    | 27.5 |
| 3145     | 150    | 400 | 285 | 424 | 1134.0   | 35.7 |
| 3146     | 200    | 500 | 340 | 509 | 2766.0   | 63.7 |

